

FLOW COEFFICIENTS

C_V VALUES

The valve flow coefficient (C_V) is a number which represents a valve's ability to pass flow. The bigger the C_V, the more flow a valve can pass with a given pressure drop. A C_V of 1 means a valve will pass 1 gallon per minute (gpm) of 60°F water with a pressure drop (Δp) of 1 (PSI) across the valve. A C_V of 350 means a valve will pass 350 gpm of 60°F water with a Δp of 1 PSI.

| Valve Size | C _V @ VARIOUS DISC ANGLES | | | | | | | Full 90° Open (C _V) |
|------------|--------------------------------------|-------|-------|-------|-------|--------|--------|---------------------------------|
| | 20° | 30° | 40° | 50° | 60° | 70° | 80° | |
| 2 | 4.06 | 14.2 | 26.3 | 44.5 | 70.6 | 105 | 135 | 159 |
| 2-1/2 | 6.17 | 20.9 | 38.6 | 65.3 | 140 | 156 | 215 | 266 |
| 3 | 13.6 | 31.4 | 57.9 | 98.0 | 156 | 240 | 342 | 457 |
| 4 | 23.9 | 55.1 | 102 | 173 | 274 | 423 | 625 | 860 |
| 5 | 37.2 | 85.6 | 158 | 268 | 426 | 656 | 970 | 1320 |
| 6 | 53.3 | 123 | 227 | 384 | 610 | 941 | 1,420 | 2,020 |
| 8 | 94.3 | 217 | 401 | 679 | 1,080 | 1,660 | 2,500 | 3,540 |
| 10 | 145 | 334 | 617 | 1,040 | 1,660 | 2,560 | 3,830 | 5,580 |
| 12 | 209 | 481 | 888 | 1,500 | 2,390 | 3,690 | 5,620 | 8,080 |
| 14 | 335 | 670 | 1,226 | 1,935 | 2,893 | 4,406 | 6,752 | 9,578 |
| 16 | 443 | 886 | 1,622 | 2,560 | 3,827 | 5,829 | 8,933 | 12,671 |
| 18 | 567 | 1,138 | 2,075 | 3,275 | 4,896 | 7,457 | 11,429 | 16,211 |
| 20 | 711 | 1,422 | 2,609 | 4,116 | 6,156 | 9,377 | 14,371 | 20,385 |
| 24 | 1,038 | 2,078 | 3,792 | 5,985 | 8,947 | 13,628 | 20,887 | 29,627 |

GENERAL NOTES

- Liquid flow data is based on pressure drop and flow rate with viscosity similar to water at 60°F using flow coefficient.
- Nomograph flow rate for gases is in cubic feet per minute (cfm) at flowing conditions. To convert flow rate from standard cu. ft. per minute to cfm, use the following formula:

$$\text{CFM} : \frac{(\text{SCFM} \times 14.7) \times (460 + ^\circ\text{F})}{(\text{line pressure, psia}) \times 520}$$

- Gas density in lbs./cu. ft., equals:

$$\frac{\left(\frac{2.70 \times}{\text{line pressure, psia}} \right) \times \left(\frac{\text{specific gravity of gas (relative to air)}}{460 + ^\circ\text{F}} \right)}$$

4. Limitations:

Do not use equations for any of the conditions listed below, please consult factory.

- For compressible fluids, where pressure (Δp) exceeds half of inlet pressure.
- For non-compressible fluids, where pressure drop causes cavitation or flashing.
- For dual-phase flow such as steam-water mixtures.

C_V = Flow coefficient for valves; expresses flow rate in gallons per minute of 60F water with 1.0 psi pressure drop across valve.

$$C_v = Q \sqrt{\frac{SQ}{(62.34)(dp)}}$$

K = resistance coefficient.

$$K = d \sqrt{\frac{29.9}{C_v}}$$

SQ = weight density of fluid, in pounds per cubic feet.

d = internal diameter of pipe, in inches.

Q = rate of flow, in gallons per minute.

dp = differential pressure, in pounds per square inch gauge.

